



DEMPSTERS 250

Adjustable Track



DRY FERTILIZER APPLICATOR | 8 TON (250 CU. FT. CAPACITY)

DEMPSTERS' TOOL-FREE 5-SECOND SPREAD PATTERN ADJUSTMENT



KEY FEATURES

- Field Adjustable Row Crop Track: 20", 30", and 36" Row Spacing
- 250 Cu. Ft. Capacity Stainless Steel Hopper, Tarp Options Available
- Sliding Walking Beam Suspension on Flotation or Narrow Tread Tires (Option)
- High & Low Range Live Axle Ground Drive with Totally Enclosed Gear Case
- Positive Metered Product Flow from Stainless Steel Conveyor System
- 60' Spread Pattern with Patented Quick and Easy Distribution Adjustment

↑ **Live Ground Drive Conveyor with 60", 68", 70" and 78" Adjustable Track Width**

📍 3283 Co Rd V, Decatur, NE 68020

🌐 hardlandequipment.com

✉ braxton@hardlandequipment.com

☎ (402) 380-9942



SPECIFICATIONS & OPTIONS

COMPONENT OPTIONS

ITEM	DESCRIPTION	
SPINNER DRIVES	PTO-540-Belt	Belt drive safety protection and shielded PTO shaft with 6-spline tractor end for 540 RPM PTO's
	PTO-540/1000	Belt drive safety protection and shielded PTO shaft with 6-spline and 21-spline tractor ends for 540 or 1000 RPM PTOs.
	Gas Engine	9 H.P. Honda gas engine with integral 12V starter-alternator and starter panel. Battery not included.
	Hydraulic	Direct-mounted spinner disc operates at optimal speed through hydraulic flow control for open or closed center tractor hydraulic systems.

TIRES & RIMS	16.5L X 16.1	10-ply implement rib tires on 8-bolt D.C. 16.1 X 14 implement rims
	9.00 X 20	10-ply narrow truck tires on 8-bolt 20 X 7 implement rims
	Rims Only	16.1 X 14 8-bolt drop center implement rim
	Rims Only	20 X 7 8-bolt drop center

ACCESSORIES

ITEM	DESCRIPTION
TARPAULIN	Heavy-duty vinyl-impregnated tarpaulin with 3" protective skirts, tailored to fit in weather-shedding "hip-roof" shape. Includes tie-downs with S-hooks. Roll top tarp also available.
BRAKES	Complete 2-wheel surge brake sets with emergency breakaway to set brakes automatically if spreader separates from tow unit. Factory installed.
HALF-RATE DRIVE	#50 roller chain reduction drive factory installed at live drive axle. Standard and half-rate stub shafts provide choice of conveyor speeds for standard or half-rate application ranges. Allows rates down to 55 lbs/acre of 60 lb./ft ³ product.

PHYSICAL DATA

DESCRIPTION	DESCRIPTION
Overall Length - Standard 209"	Spreader Fan Height on 16.5L 28"
Overall Height with Tarp 96"	on 9.00 tires..... 28"
Overall Width w/ 16.5L tires 98"	Adjustable Tread Width - Center to Center..... 60" ,68" , 70" & 78"
w/ 9.00 tires..... 96"	
Hopper Length 108"	Approximate Weight: Stainless Steel Unit 3200 lbs.
Width 94"	



60' Spread Pattern (up to 90')



Dempsters' Tool-Free 5-Second Adjustable Spread Pattern